

JTCSOL450UV

## Technical Data Sheet Jet-Text-Canvas 450SOL/UV

450 gr/m<sup>2</sup> woven Cotton-Polyester based Canvas Media for Eco- and True-Solvent Inks and also for UV-curable systems

### Product Characteristics

JET TEX CANVAS 450SOL is made of a woven Cotton- Polyester-Structure for Eco- and True-Solvent Inkjet Printing and also suitable for UV-Curable Machines.

Fully coated for very high Image Quality, excellent Tear Resistance and Flexible. Dimensionally and mechanically stabile, for all suitable Applications. The Coating enables high ink applications with very rapid drying.

High Colour-Brilliance and a satin finish after printing. .

Available Roll Formats - 0,914m, 1,067m, 1,27m 1,37m und 1,54m width  
Roll Length in - 12m available

### Applications & Handling

Single Side has a special Top-Coating, enabling a high image quality. The coating is splash-water resistant, rapid drying no bleeding

Ideal for photo-imaging, fine-art reproduction and framed pictures

We recommend you perform a length calibration test before printing if possible

### Physical Properties:

Raw.-Mat: PET/Cotton  
Opacity: > 90%  
Temp.-Resist.: -30° - + 50° C  
Ghaugue/Weight: 450g/m<sup>2</sup>

### Conditions of use/storage:

Operating Temp: 18° - 25° C  
Rel. Humidity: 40% - 65%  
Storage Time: min. 1 Years



### PRINTING-Systems

Piezo Printers Dye based Ink  
Piezo Printers Pigment based Ink  
Bubble Jet Printers Dye based Ink  
Bubble Jet Printers Pigment based Ink  
Eco-Solvent Printers  
Hard-Solvent Printers  
Uv-curable Printers

### Kompatibility



NOPAR International GmbH  
Ludwig-Erhard-Str. 18

D-28197 Bremen  
PHONE: +49 421 52081460  
FAX: +49 421 52081469

For available printer, lamination & profile settings - Please contact:  
[info@nopar-international.com](mailto:info@nopar-international.com)

Please note that all information supplied is correct to date of print, information can change without prior notification. This information does not release the manufacturer from his obligation with regard to proper application and handling of the product. All content is based on available technical knowledge at the time of publication.