

JTCWR500

## Technical Data Sheet Jet-Text-Canvas 500WR

500 gr/m<sup>2</sup> 100% Cotton based Canvas Media for waterbased Inks

### Product Characteristics

JET TEX CANVAS 500WR is made of a 100% woven Cotton for waterbased Inkjet Printing (Dye and pigmented).

Fully coated for very high Image Quality, excellent Tear Resistance and Flexible. Dimensionally and mechanically stabile, for all suitable Applications. The Coating enables high ink applications with very rapid drying.

High Colour-Brilliance and a satin finish after printing..

Available Roll Formats - 0,914m, 1,067m, 1,27m 1,37m und 1,54m width  
Roll Length in - 15m available

### Applications & Handling

Single Side has a special Top-Coating, enabling a high image quality. The coating is splash-water resistant, rapid drying no bleeding

Ideal for photo-imaging, fine-art reproduction and framed pictures

We recommend you perform a length calibration test before printing if possible



### Physical Properties:

Raw.-Mat: Cotton  
Opacity: > 90%  
Temp.-Resist.: -30° - + 50° C  
Ghaugue/Weight: 500g/m<sup>2</sup>

### Conditions of use/storage:

Operating Temp: 18° - 25° C  
Rel. Humidity: 40% - 65%  
Storage Time: min. 1 Years

### PRINTING-Systems

### Kompatibility

Piezo Printers Dye based Ink	<input checked="" type="checkbox"/>
Piezo Printers Pigment based Ink	<input checked="" type="checkbox"/>
Bubble Jet Printers Dye based Ink	<input checked="" type="checkbox"/>
Bubble Jet Printers Pigment based Ink	<input checked="" type="checkbox"/>
Eco-Solvent Printers	
Hard-Solvent Printers	
Uv-curable Printers	

NOPAR International GmbH  
Ludwig-Erhard-Str. 18

D-28197 Bremen  
PHONE: +49 421 52081460  
FAX: +49 421 52081469

For available printer, lamination & profile settings - Please contact:  
[info@nopar-international.com](mailto:info@nopar-international.com)

Please note that all information supplied is correct to date of print, information can change without prior notification. This information does not release the manufacturer from his obligation with regard to proper application and handling of the product. All content is based on available technical knowledge at the time of publication.