

JFTWR

Technisches Datenblatt Jet Folio Tacklite Signage Film

230 µm **matte white PE/PP polymer adhesion Ink Jet Film**
(Water-resistant Coating)

Product Characteristics

Special natural polymer adhesion surface on the reverse that has been developed without the use of adhesive or chemical agents, for Vehicle Graphics, Window Signage, Display Graphics
The raw material has been exclusively manufactured, developed and supplied for the car protection industry originally.

Special natural polymer adhesion surface on the reverse that has been developed without the use of adhesive chemical agents

"No residue" is left on the correct application surface when removed.
Supplied with a water-resistant ink jet coated surface

Available Rollformats – 36" 42" larger Sizes on request

Applications & Handling

Caution: When the product is applied to PVC/Vinyl or Glossy Aluminium the adhesion becomes permanent. If used for the above applications then the product can be removed and the surface cleaned with standard acetone products On Polyester lacquers, stainless steel and soft PVC the special reverse polymer adhesion can become permanent when subject to a high concentration of heat. For raw metal surfaces under extreme heat, a strong adhesion and peeling force should be expected. We recommend that you pre-test your application surface prior to actual application
If an over-laminate is required, then we recommend Cold Lamination. Not developed for true re-positionable applications

Physical Properties:

Thickness: 230 µm
Opacity: > 95%
Media Colour: L 94,4
a -0,07
b -2,58

Conditions of use/storage:

Operating Temp: 15° - 45° C
Rel. Humidity: 40% - 65%
Storage Time: min. 2 Years



Printer	Inks Dye Based	Inks Pigmented
Agfa Sherpa /Montana	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
ColorSpan Serie XII	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Encad Novajet all	<input checked="" type="checkbox"/> GS+ /GX	<input checked="" type="checkbox"/>
HP Designjet all	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
EPSON all	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Mimaki all	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Muthoh all	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
ROLAND all	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

NOPAR International GmbH
Ludwig-Erhard-Str. 18

D-28197 Bremen
PHONE: +49 421 52081460
FAX: +49 421 52081469

For available printer, lamination & profile settings - Please contact:
info@nopar-international.com

Please note that all information supplied is correct to date of print, information can change without prior notification. This information does not release the manufacturer from his obligation with regard to proper application and handling of the product. All content is based on available technical knowledge at the time of publication.